

PROXIMITY READER CONTROL UNIT EVE196-X3-RS



REAL TIME



Anti-clone
Guarantee



Remote access




KEY FEATURES...

- MIFARE 13.56MHz proximity keys
- 3000 proximity key capacity
- Networkable device
- Time zone control
- 8 week types
- Email alerts
- Real time remote management
- Proximity keys with Anti-Clone Protection

PROXIMITY READER ACCESS CONTROL

REFERENCE	EVE196-X3-RS
MECHANICAL CHARACTERISTICS	
Dimensions (HxWxD)	85 x 53 x 20 mm
Weight	80 g
Material	ABS
Screw fixings	M3 screws
ELECTRICAL CHARACTERISTICS	
Voltage	12VDC-18VDC
Consumption	225mA max (whilst relay is activated)
Relay	1no 5 Amp rated NO/NC programmable
Operating temperature	-10°C to +55°C
Norms	EN50082 / EN55022
FEATURES	
Bus	Max length 400 metres using Class E (CAT6) U/UTP in series
Device capacity	3000 proximity keys
Input	1no for exit button
Integral timeclock	Synchronises automatically with baticonnect.com
Alert	Email
Programming	www.baticonnect.com available 24/7/365



Secured by Design



Police Preferred Specification



24/7/365

www.baticonnect.com

08000 156496
 sales@ipdooreentry.co.uk
 www.ipdooreentry.co.uk
 f ipdooreentry

IP Door Entry Limited
 Unit DC4 Prologis Park
 Eastman Way
 Hemel Hempstead
 HP2 7DU