



4G/IP SMART VISITOR DOOR ENTRY







KEY FEATURES...

- > HD pinhole colour camera
- > TFT colour screen 2.9 inches
- > Anti-vandal proximity reader, illuminated
- Integrated 4G modem antenna
- > Robust 3mm dia aluminium facia
- > Equality Act 2010 Compliant
- Mobile access via smart app

SPECIFICATIONS	SILVER	CHAMPAGNE	MATT BLACK
REFERENCES	TP4G-AX	TP4G-DX	TP4G-NX
MECHANICAL CHARACTERISTICS			
Facia dimensions (HxWxD)	270 x 120 x 14 mm		
Backbox dimensions (HxWxD)	245 x 95 x 45 mm		
Material	Aluminium		
Finish	Brushed anodised - Silver	Brushed anodised - Champagne	Brushed anodised - Black
Protection rating	IK09 / IP54		
ELECTRICAL CHARACTERISTICS			
Power	12 V DC		
Consumption	2A max (whilst communicating via 4G)		
Relay	1 relay 5 Amp rated NO/NC programmable		
Temperature	Operating -25°C to 70°C / Storage -40°C to 85°C		
FEATURES			
Colour camera	Pinhole hidden, angle of view H 60°, V 45°		
Screen	TFT colour 2.9"		
Proximity reader	Anti-vandal makrolon, illuminated		
Keypad	12 large (15.6mm dia) backlit braille keys		
Capacity	3000 flats		
Inputs	2 no (direct call, relay control)		
Smartphone App	IPGUARD APP on Google Play (Android), App Store (APPLE)		
Programming	WWW.BATICONNECT.COM available 24/7/365 real time		
Mobile access	Open door via app on smart devices from anywhere, at any time		
Advanced features	Customisable welcome screen – Backlight compensation – Proximity key & radio transmitter ANTI-CLONE guarantee – Smartphone access		



Champagne Surface



TP4G-DX + BSD3

Champagne Flush



TP4G-DX

Surface housing



BSD3

Silver Surface



TPG4G-AX + BSA3

Silver Flush



TP4G-AX

Surface Housing



BSA3







TO SELECT WHO TO CALL
ENTER A + FLAT/APT NUMBER

A>Z Z>A Search
Q

WELCOME SCREEN

SCROLL SCREEN

DIRECT CALL SCREEN

Alternates every few seconds.



SEARCH SCREEN

Very useful in mixed residential/ commercial, and gated sites with mix of house names and flat numbers.



DISPLAYS FLAT TO CALL



VISUAL INFORMATION IN ADDITION TO VOICE MESSAGE

Switches to green for Door Open, red for Denied.



IPGUARD MINI 4G/IP	
TP4G-AX	Silver
TP4G-DX	Champagne
TP4G-NX	Matt black

KIT, IPGUARD MINI 4G/IP + CONTROL UNIT (EVE196-X3-RS) FOR PROXIMITY READER			
DTP4G-AXEZ	Silver		
DTP4G-DXEZ	Champagne		
DTP4G-NXEZ	Matt black		

ACCESSORIES			
PSU	AR125	12V-5A DIN rail	
SURFACE BOXES	BSA3	Surface housing silver	
	BSD3	Surface housing champagne	
	BSN3	Surface housing matt black	
SECURITY TOOL	ZVTE1050	Security tool	
AERIAL	ZAN1055	Remote aerial including 5m cable	
ROUTER	IGSM4G01	4G router, max distance 80 metres from panel using Class E (CAT6) U/UTP cable	
EXTENSION CABLES *	ZCAB54-M	Cable for remote aerial (5 metres)	
	ZCAB53-M	Cable for remote aerial (10 metres)	
	ZCAB52-M	Cable for remote aerial (15 metres)	

IPGUARD MINI PLUS 4G/IP SMART TECHNOLOGY

120 mm







MATT BLACK



270 mm

