



4G/IP SMART VISITOR DOOR ENTRY





Mobile access via smart app

SPECIFICATIONS	STAINLESS STEEL	BRASS 🛑
REFERENCES	TP4G-IX	TP4G-LX
MECHANICAL CHARACTERISTICS		
Facia dimensions (HxWxD)	280 x 120 x 3 mm	
Backbox dimensions (HxWxD)	254 x 95 x 60 mm	
Material	Stainless Steel 316	Brass
Finish	Brushed	
Protection rating	IK09 / IP54	
ELECTRICAL CHARACTERISTICS		
Power	12 V DC	
Consumption	2A max (whilst communicating via 4G)	
Relay	1 relay 5 Amp rated NO/NC programmable	
Temperature	Operating -25°C to 70°C / Storage -40°C to 85°C	
FEATURES		
Colour camera	Pinhole hidden, angle of view H 60°, V 45°	
Screen	TFT colour 2.9"	
Proximity reader	Anti-vandal makrolon, illuminated	
Keypad	12 large (15.6mm dia) backlit braille keys	
Capacity	3000 flats	
Inputs	2 no (direct call, relay control)	
Smartphone App	IPGUARD APP on Google Play (Android), App Store (APPLE)	
Programming	WWW.BATICONNECT.COM available 24/7/365 real time	
Mobile access	Open door via app on smart devices from anywhere, at any time.	
Advanced features	Customisable welcome screen – Backlight compensation – Proximity key & radio transmitter ANTI-CLONE guarantee – Smartphone access – Hearing aid loop	

> Hearing aid loop

> Hands-free Bluetooth proximity reader



IPGUARD MINI PLUS 4G/IP

TP4G-IX	Stainless steel, flush
TP4G-LX	Brass, flush

KIT, IPGUARD MINI PLUS 4G/IP + CONTROL UNIT (EVE196-X3-RS) FOR PROXIMITY READER

DTP4G-IX	Stainless steel, flush
DTP4G-LX	Brass, flush

ACCESSORIES			
PSU	AR125	12V-5A DIN rail	
SURFACE BOXES Special order		Surface housing stainless steel	
		Surface housing brass	
SECURITY TOOL	ZVTE1050	Security tool	
AERIAL	ZAN1055	Remote aerial including 5m cable	
ROUTER	IGSM4G01	4G router, max distance 80 metres from panel using Class E (CAT6) U/UTP cable	
EXTENSION CABLES *	ZCAB54-M	Cable for remote aerial (5 metres)	
	ZCAB53-M	Cable for remote aerial (10 metres)	
	ZCAB52-M	Cable for remote aerial (15 metres)	

IPGUARD MINI PLUS 4G/IP SMART TECHNOLOGY

280 mm

120 mm







BRUSHED BRASS



